

# Product Specification Sheet



## PRO-TEK SB 190                      Cleaning & Descaling Products

**PRO-TEK 190** is an uninhibited dry powder acid based on sulphamic acid. **PRO-TEK 190** has the advantage of safe and convenient storage and handling, whilst generating a strong chemical cleaning acid in aqueous solution. Solutions of this product are safe to use up to 60 Degrees Celsius.

### PRODUCT SPECIFICATION

Property Description	Property Value/Quality
SBS 190	
Appearance	White solid
SG	NA
pH	3.5 (5% solution)

\* other details as well as MSDS available on request.

### DISTRIBUTION

**Oil & Water Supplies Limited**  
111 Union Street  
Glasgow , G1 3TA  
United Kingdom  
Tele:+44 141 221 7834  
Mob:+44 7789 958420  
Fax: +44 141 626 1430  
Email: [sales@owsupplies.biz](mailto:sales@owsupplies.biz)

### ANALYTICAL TESTING

Cleaning Solution pH by means of a standard calibrated pH meter.

### CERTIFICATION / APPROVAL

ISO 9001 : 2000 Approved

### DOSING

**PRO-TEK 190** should be dissolved in fresh clean water at a concentration of 5-20% V/V dependent on the level of scale within the system. The resulting solution should remain in the system for a period of 2-6 hours. If the system undergoing treatment is a boiler it is imperative that the boiler IS NOT FIRED until the cleaning solution has been discharged and the boiler completely flushed with fresh water.

### HANDLING / SAFETY

The handling of any chemical requires care. Anyone responsible for using or handling SB 190 should familiarize themselves with the full safety precautions outlined in our Material Safety Data Sheet.

### PACKAGING

Available in 25 KG drums.

### STORAGE

Store in a dry, cool well ventilated area