

Product Specification Sheet



Product: PRO-TEK FLB 4550 SEP

PRO-TEK FLB 4550 SEP is a DADMAC Alum blend suitable for potable water applications. PRO-TEK FLB 4550 SEP performs the same function as our competitor products sulfloc & algefloc. Three versions are available, the last two numbers indicate the percentage of Poly DADMAC, we can also offer 4540 SEP & 4525 SEP

PRODUCT SPECIFICATION

Property Description	Property Value/Quality
Form	liquid
Colour	yellow to amber
Ionic Character	Cationic
Charge Density	Very-high
Specific Gravity	1.25 - 1.40
pH	0.5 - 2.0
Brookfield viscosity (cps)**	500 - 1000
Stability of D.I. solution	5 hours
Freezing point (°C)	< -10
Total solids (%)	23 - 27
AL ₂ O ₃ content (%)	11.5 - 13.5
Storage temperature (°C) :	0 - 30
Shelf life	6 months

* other details as well as MSDS available on request.

DISTRIBUTION

Oil & Water Supplies Limited

Forsyth House
111 Union Street
Glasgow , G1 3TA
United Kingdom
Tele:+44 141 221 7834
Mob:+44 7789 958420
Fax: +44 141 626 1430

Email: sales@owsupplies.biz

CERTIFICATION / APPROVAL

ISO 9001 : 2000 Approved

DOSING

Dosing is dependant on individual requirement. Though we can assist in dosage requirement, given correct information.

HANDLING / SAFETY

The handling of any chemical requires care. Anyone responsible for using or handling PRO-TEK FLB 4550 SEP should familiarize themselves with the full safety precautions outlined in our Material Safety Data Sheet.

Avoid spilling.

STORAGE

Store in a dry, cool well ventilated area

PACKAGING

Plastic Pails 5Kgs & 25Kgs
Drums 250Kgs
IBC 1,100Kgs

Please Note, we also supply a full range of Water treatment Chemicals, please visit our Web site @ www.owsupplies.biz for more details